

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE  
REQUEST FOR FILING NATIONAL PATENT APPLICATION

Under 35 USC 111(a) and Rule 53(b)

PATENT APPLICATION

Asst. Commissioner of Patents  
Washington, D.C. 20231

WITH SIGNED DECLARATION

jc639 U.S. PTO  
12/23/99

NONPROVISIONAL  
NON REISSUE  
NON PCT NAT PHASE

jc511 U.S. PTO  
09/472134  
12/23/99

Sir:

Herewith is the PATENT APPLICATION of  
Inventor(s): GIROUARD, et al.

Title SNOWMOBILE

Atty. Dkt.: PM 265136  
M#

Client Ref

including:

Date: December 23, 1999

1. Specification: 27 pages (only spec. and claims) 2. ☐ Specification in non-English language  
3. Declaration ☐ Original ☒ Facsimile/Copy ☒ Abstract 1 page(s); 83 numbered claims  
4. ☒ Drawings: 20 sheet(s) ☐ informal; ☒ formal of size: ☒ A4 ☐ 11"  
5. ☒ See top first page re prior Provisional, National or International application(s). ("X" box only if info is there and do not complete corresponding item 5 or 6). (Prior M# 9919/243024 SN 60/167,614 )  
6. **AMEND the specification** please by inserting before the first line: -- This is a ☐ Continuation-in-Part  
☐ Divisional ☐ Continuation ☐ Substitute Application (MPEP 201.09) of:  
6(a) ☐ National Appln. No. / filed . (M# )  
6(b) ☐ International Appln. No. filed  
7. ☐ **AMEND the specification** by inserting before the first line: -- This application claims the benefit of U.S.  
Provisional Application No. 60/ , filed . --  
8. ☐ Attached is an assignment and cover sheet. Please return the recorded assignment to the undersigned.  
9. ☐ Prior application is assigned to

by Assignment recorded Reel Frame

10. **FOREIGN** priority is claimed under 35 USC 119(a)-(d)/365(b) based on filing in CANADA

11. (country)

Application No.	Filing Date	Application No.	Filing Date
(1) 2,256,944	December 23, 1998	(2)	
(3)		(4)	
(5)		(6)	
(7)		(8)	
(9)		(10)	

12. 1 (No.) Certified copy (copies): ☒ attached; ☐ previously filed (date)   
in U.S. Application No. / filed on

13. ☐ Attached: \_\_\_\_\_ (No.) Verified Statement(s) establishing "small entity" status under Rules 9 & 27.
14. **DOMESTIC/INTERNATIONAL** priority is claimed under 35 USC 119(e)/120/365(c) based on the following provisional, nonprovisional and/or PCT international application(s):

Application No.	Filing Date	Application No.	Filing Date
(1) 60/167,614	November 26, 1999	(4)	
(2)		(5)	
(3)		(6)	

15. ☐ This application is being filed under Rule 53(b)(2) since an inventor is named in the enclosed Declaration who was not named in the prior application.
16. ☐ Attached:
17. ☐ Preliminary Amendment:

**THE FOLLOWING FILING FEE IS BASED ON CLAIMS AS FILED LESS ANY ABOVE CANCELLED**

				Large/Small Entity		Fee Code
18. Basic Filing Fee				\$760/\$380	\$760	101/201
19. Total Effective Claims	88	minus 20 =	*68	x \$18/\$9 =	+ 1224	103/203
20. Independent Claims	27	minus 3 =	*24	x \$78/\$39 =	+ 1872	102/202
*If answer is zero or less, enter "0"						
21. If any proper multiple dependent claim (ignore improper) is present, add (Leave this line blank if this is a reissue application)				+ \$260/\$130	+ 260	104/204
22. TOTAL FILING FEE ENCLOSED =					\$4116	
23. If "non-English" box 2 is X'd, add Rule 17(k) processing fee				+ \$130	+ 0	139
24. If "assignment" box 8 is X'd, add recording fee				+ \$40	+ 0	581
25. <input type="checkbox"/> Attached is a Petition/Fee under Rule No.				+ \$130	+ 0	122
26. TOTAL FEE ENCLOSED =					\$4116	

Our Deposit Account No. 03-3975

Our Order No. 9919      265136  
C#      M#

**CHARGE STATEMENT:** The Commissioner is hereby authorized to charge any fee specifically authorized hereafter, or any missing or insufficient fee(s) filed, or asserted to be filed, or which should have been filed herewith or concerning any paper filed hereafter, and which may be required under Rules 16-18 (missing or insufficient fee only) now or hereafter relative to this application and the resulting Official document under Rule 20, or credit any overpayment, to our Account/Order Nos. shown above for which purpose a duplicate copy of this sheet is attached.

This CHARGE STATEMENT does not authorize charge of the issue fee until/unless an issue fee transmittal form is filed.

**Pillsbury Madison & Sutro LLP**  
**Intellectual Property Group**

1100 New York Avenue, NW  
Ninth Floor  
Washington, DC 20005-3918  
Tel: (202) 861-3000  
KDJ/tlm

By Atty: Jeffrey D. Karceski

Reg. No. 35914

Sig: 

Fax: (202) 822-0944  
Tel: (202) 861-3660

NOTE: File in duplicate with 2 post card receipts (PAT-103) & attachments

# APPLICATION UNDER UNITED STATES PATENT LAWS

Atty. Dkt. No. PM 9919/265136  
(M#)

Invention: SNOWMOBILE

Inventor (s): Bruno GIROUARD  
Berthold FECTEAU

Pillsbury Madison & Sutro LLP  
Intellectual Property Group  
1100 New York Avenue, NW  
Ninth Floor  
Washington, DC 20005-3918  
Attorneys  
Telephone: (202) 861-3000

This is a:

- ☐ Provisional Application
- ☒ Regular Utility Application
- ☐ Continuing Application
- ☐ PCT National Phase Application
- ☐ Design Application
- ☐ Reissue Application
- ☐ Plant Application
- ☐ Substitute Specification

Sub. Spec Filed \_\_\_\_\_  
in App. No. / \_\_\_\_\_

## SPECIFICATION

## SNOWMOBILE

This application claims the benefit of U.S. Provisional Patent Application No. 60/167,614, which was filed on November 26, 1999, which is incorporated herein by reference. This application also claims the benefit of priority to Canadian Patent Application No. 2,256,944, filed on December 23, 1998, which is incorporated herein by reference.

### Field of the Invention

The present invention concerns the overall design and construction of a snowmobile. More particularly, the present invention concerns a design for a snowmobile where, among other features, the steering control position, the seating position, and the position of the footrests are arranged in relation to one another so that the rider's center of gravity is closer to the center of gravity of the vehicle than on a conventional snowmobile. Moreover, the design for the snowmobile of the present invention improves the rider's control over the vehicle.

### Background of the Invention

Conventional snowmobiles share a common construction: they combine features and elements so that the rider sits in a generally upright position in a location toward the rear of the vehicle. When seated in this fashion, the rider sits a considerable distance behind the center of gravity of the vehicle (*i.e.*, the center of gravity of the combination of the vehicle and the rider), which is located at or in proximity to the axis of the forward-most axle of the drive track.

When a snowmobile encounters a bump as it travels over the ground, the vehicle naturally tends to pivot about its center of gravity. Accordingly, the further the rider is positioned from the center of gravity of the vehicle, the more strongly the rider will feel each bump as he passes over it. This occurs because the vehicle acts as a lever that amplifies the magnitude of the forces transferred from bumps on the ground to the rider. In the case of the conventional snowmobile, because the rider is positioned toward the rear of the vehicle, the rider is acutely aware of this phenomenon.

Accordingly, while the positioning of the rider on the conventional snowmobile is entirely adequate for enjoying the sport of snowmobiling, a need has arisen for a snowmobile where the rider's position is improved to minimize the effect of the vehicle's movement on the rider as it passes over uneven terrain.

### Summary of the Invention

The present invention improves upon the conventional design by repositioning the rider on the vehicle and redesigning the layout of the vehicle to minimize the effect of the vehicle's movement on the rider as they pass over uneven terrain.

As would be understood by a person skilled in the art, a snowmobile has a center of gravity without the rider, and may have a different center of gravity with the rider. In the context of the present application it should be understood that the expression "center of gravity of a snowmobile" refers the center of gravity of a snowmobile with the rider, unless the contrary is indicated. Further, it should be understood that in the context of the present invention it is assumed that the vehicle is in running condition and is full of fuel.

The present invention provides a snowmobile with a frame and an engine disposed on the frame. A drive track is disposed below the frame and connected operatively to the engine for propulsion of the snowmobile. At least one ski is disposed on the frame and a seat is disposed rearwardly of the engine, suitable for a rider with a center of gravity. A steering device is disposed above the engine and forward of the seat and is operatively connected to the at least one ski for steering the snowmobile.

In one aspect, a distance  $a$  between a vertical line passing through the center of gravity of the snowmobile without the rider and a vertical line passing through the center of gravity of the snowmobile with the rider is preferably between about 0 and 14 cm. More preferably, distance  $a$  is between about 2 and 12 cm. Still more preferably, distance  $a$  is between about 4 and 10 cm. Still more preferably, distance  $a$  is between about 5 and 7 cm. Most preferably distance  $a$  is about 5 cm.

In another aspect, a distance  $z$  between a vertical line passing through the forward-most drive track axle (usually, but not exclusively the drive axle) and a vertical line passing through the center of gravity of the rider is preferably between about 15 and 65 cm. More preferably, distance  $z$  is between about 25 and 55 cm. Still more preferably, distance  $z$  is between about 35 and 55 cm. Still more preferably, distance  $z$  is between about 37 and 47 cm. Most preferably distance  $z$  is about 40 cm or about 45 cm.

In yet another aspect, a distance  $x$  between a vertical line passing through the center of gravity of the snowmobile with the rider and a vertical line passing through the center of gravity of the rider is preferably between about 0 and 50 cm. More preferably, distance  $x$  is between about 10 and 40 cm. Still more preferably, distance  $x$  is between about 22 and 32 cm. Most preferably, distance  $x$  is about 25 cm or about 30 cm.

In still yet another aspect, a distance  $y$  between a vertical line passing through the center of gravity of the snowmobile without the rider and a vertical line passing through the center of gravity of the rider is preferably between about 5 and 55 cm. More preferably, distance  $y$  is between about 15 and 45 cm. Still more preferably, distance  $y$  is between about 25 and 45 cm or between about 27 and 37 cm. Most preferably, distance  $y$  is about 30 or 35 cm.

Also in accordance with the teachings of the present invention, a snowmobile is provided that has a frame with an engine disposed thereon. A drive track is disposed below the frame and connected operatively to the engine for propulsion of the snowmobile. At least one ski is disposed on the frame. A seat is disposed rearwardly of the engine, suitable for a rider having a center of gravity, and a

steering device is disposed forward of the seat. The steering device is operatively connected to the at least one ski for steering the snowmobile.

In one aspect, the snowmobile has a center of gravity positioned so that a line passing through the center of gravity of the snowmobile without the rider and the center of gravity of the snowmobile with the rider preferably forms an angle  $\lambda$  with horizontal that is between about 35 and 90°. More preferably, angle  $\lambda$  is between about 50 and 90°. Still more preferably, angle  $\lambda$  is between about 62 and 90°. Most preferably, angle  $\lambda$  is about 67°.

In another aspect, the snowmobile has a center of gravity positioned so that a line passing through the forward-most drive track axle and the center of gravity of the rider preferably forms an angle  $\pi$  with horizontal that is between about 41 and 75°. More preferably, angle  $\pi$  is between about 45 and 65°. Still more preferably, angle  $\pi$  is between about 50 and 60°. Most preferably, angle  $\pi$  is about 55°.

In still another aspect, the snowmobile has a center of gravity positioned so that a line passing through the center of gravity of the snowmobile without the rider and the center of gravity of the rider preferably forms an angle  $\omega$  with horizontal that is between about 39 and 79°. More preferably, angle  $\omega$  is between about 49 and 69°. Still more preferably, angle  $\omega$  is between about 54 and 64°. Most preferably, angle  $\omega$  is about 59°.

In yet another aspect, the snowmobile has a center of gravity positioned so that a line passing through the center of gravity of the snowmobile with the rider and the center of gravity of the rider preferably forms an angle  $\theta$  with horizontal that is between about 35 and 84°. More preferably, angle  $\theta$  is between about 45 and 75°. Still more preferably, angle  $\theta$  is between about 55 and 70°. Most preferably, angle  $\theta$  is about 57°.

According to further teachings of the present invention, a snowmobile is provided having a frame on which a seat is disposed that is suitable for a rider. A steering device is disposed on the frame forward of the seat. Right and left footrests are disposed below the seat on either side thereof, suitable for placement of a rider's feet thereon. The steering device defines a steering position, the seat defines a seat position, and the footrests define a footrest position. A line passing through the seat position and the steering position forms angle  $\alpha$  with a line passing through the seat position and the footrest position. A line passing through the footrest position and the steering position forms angle  $\beta$  with the line passing through the footrest position and the seat position. Finally, the line passing through the footrest position and the steering position forms angle  $\gamma$  with the line passing through the steering position and the seat position. Preferably, angle  $\alpha$  is between about 63 and 152°, angle  $\beta$  is between about 16 and 84°, and angle  $\gamma$  is between about 11 and 42°. More preferably, angle  $\alpha$  is between about 67 and 112°, angle  $\beta$  is between about 41 and 72°, and angle  $\gamma$  is between about 22 and 45°. Still more preferably, angle  $\alpha$  is between about 75 and 97°, angle  $\beta$  is between about 52 and 67°, and angle  $\gamma$  is

between about 30 and 41°. Most preferably, angle  $\alpha$  is about 83°, angle  $\beta$  is about 64°, and angle  $\gamma$  is about 33°.

According to additional teachings of the present invention, a snowmobile is provided with a frame and a seat disposed on the frame, suitable for a rider. A steering device is disposed on the frame forward of the seat. Right and left footrests are disposed below the seat on either side thereof, suitable for placement of the rider's feet thereon. The seat defines a seat position, the steering device defines a steering position, and the footrests define a footrest position. A line passing through the seat position and the steering position forms angle  $\alpha$  with a line passing through the seat position and the footrest position, a line passing through the footrest position and the steering position forms angle  $\beta$  with the line passing through the footrest position and the seat position, the line passing through the footrest position and the steering position forms angle  $\gamma$  with the line passing through the steering position and the seat position, and angle  $\alpha$ , angle  $\beta$ , and angle  $\gamma$  satisfy the relationship  $\alpha \geq \beta \geq \gamma$ .

According to still further teachings of the present invention, a snowmobile is provided that has a frame and a seat disposed on the frame, suitable for a rider. A steering device is disposed on the frame forward of the seat. Right and left footrests are disposed below the seat on either side thereof, suitable for placement of the rider's feet thereon. The seat defines a seat position, the steering device defines a steering position, and the footrests define a footrest position. A line passing through the seat position and the steering position forms angle  $\alpha$  with a line passing through the seat position and the footrest position. A line passing through the footrest position and the steering position forms angle  $\beta$  with the line passing through the footrest position and the seat position. The line passing through the footrest position and the steering position forms angle  $\gamma$  with the line passing through the steering position and the seat position. Angle  $\alpha$ , angle  $\beta$ , and angle  $\gamma$  satisfy the relationship: angle  $\alpha \approx 2.5\gamma$ .

A snowmobile is also provided with a frame and a seat disposed on the frame. A steering device is disposed on the frame forward of the seat. The seat defines a seat position and the steering device defines a steering position. A line passing through the steering position and the seat position forms an angle  $\phi$  with horizontal that is between about 15 and 51°. More preferably, angle  $\phi$  is between about 19 and 41°. Even more preferably, angle  $\phi$  is between about 23 and 31°. Most preferably, angle  $\phi$  is about 26°.

The present invention also provides for a snowmobile having a frame and at least one ski disposed on the frame. A steering shaft is operatively connected to the at least one ski for steering the snowmobile. The steering shaft is disposed over the engine at an angle  $\epsilon$  of less than about 45° from vertical. More preferably, angle  $\epsilon$  is between about 25 and 40° from vertical. Even more preferably, angle  $\epsilon$  is between about 30 and 35° from vertical. Most preferably, angle  $\epsilon$  is about 33° from vertical.

According to still further teachings of the present invention, a snowmobile is provided with a frame and a seat disposed on the frame, suitable for a rider, the seat defining a location of a rider space associated with the seat. A steering shaft is disposed on the frame forward of the seat and a handlebar is mounted onto the steering shaft. The handlebar and steering shaft are rotatable about a central axis

between first and second positions to define a handlebar space. The handlebar space does not intersect with the rider space.

According to further teachings of the present invention, a snowmobile is provided having a frame, a seat disposed on the frame, suitable for a rider, a steering device disposed forward of the seat, and a windshield disposed forward of the steering device, the windshield having a top. The steering device defines a steering position and the seat defines a seat position. A line between the steering position and the seat position forms an angle  $\mu$  with a line between the seat position and the top of the windshield that lies between about 0 and 20°. More preferably, angle  $\mu$  is between about 10 and 20°. Most preferably, angle  $\mu$  is about 18°.

The teachings of the present invention also provide for a snowmobile having a frame and a seat disposed on the frame, suitable for a rider. A steering device is disposed forward of the seat. A windshield having a top is disposed forward of the seat. When in motion, the windshield defines a laminar flow region of moving air that extends upwardly and rearwardly from the top thereof. When seated in the seat and when grasping the steering device, the rider's head is positioned within the laminar flow region.

According to still further teachings of the present invention, a snowmobile is provided with a frame, a drive axle disposed on the frame, and a steering device disposed on the frame forward of the drive axle.

In addition, the present invention provides for a snowmobile with a frame, a seat disposed on the frame, suitable for a rider, and right and left footrests disposed below the seat on either side thereof, suitable for placement of the rider's feet thereon. A steering device is disposed forward of the footrests.

The present invention also provides for a snowmobile with a frame, a seat disposed on the frame, and a steering device disposed on the frame and forward of the seat. A distance  $b$  between vertical lines passing through the steering device and the seat is between about 40 and 90 cm. More preferably, distance  $b$  is between about 50 and 80 cm. Still more preferably, distance  $b$  is between about 60 and 80 cm. Most preferably, distance  $b$  is about 65 or 70 cm.

According to still further teachings of the present invention, a snowmobile is provided with a frame, a seat disposed on the frame, suitable for a rider, and right and left footrests disposed below the seat on either side thereof, suitable for placement of the rider's feet thereon. The footrests are disposed at an angle  $\Delta$  with horizontal that is between about + 10 and - 20°. More preferably, angle  $\Delta$  is between about + 10 and - 10°. Still more preferably, angle  $\Delta$  is between about 0 and - 5°. Most preferably, angle  $\Delta$  is about - 5°.



### Brief Description of the Drawings

For a better understanding of the present invention as well as other objects and further features thereof, reference is made to the following description which is to be used in conjunction with the accompanying drawings, where:

FIG. 1 is a side view illustration of a conventional snowmobile, showing the traditional positioning of a rider thereon;

FIG. 2 is a perspective view of the snowmobile according to the teachings of the present invention, showing the positioning of a rider thereon;

FIG. 3 is a side view illustration of a conventional snowmobile and the snowmobile of the present invention superimposed on one another to illustrate the differences therebetween;

FIG. 4 is a top view representation of a snowmobile constructed according to the teachings of the present invention, showing the radius of travel of the steering device through a full range of motion;

FIG. 5 is a side view illustration of the positioning of the rider on the snowmobile of the present invention (which is not shown), showing the angular relationship between the steering position, the seat position, and the footrest position;

FIG. 6 is a side view illustration of the position of the rider on the snowmobile of the present invention as illustrated in FIG. 5, showing distances  $a$ ,  $x$ ,  $y$ , and  $z$  between various points;

FIG. 7 is a side view illustration of the position of the rider on the snowmobile of the present invention, showing angle  $\lambda$  formed by a line through the center of gravity of the vehicle with and without the rider and horizontal;

FIG. 8 is a side view illustration of the position of the rider on the snowmobile of the present invention, showing angle  $\pi$  formed by a line between the forward-most drive axle and the rider's center of gravity and horizontal;

FIG. 9 is a side view illustration of the position of the rider on the snowmobile of the present invention, showing angle  $\omega$  formed between a line between the center of gravity of the vehicle without the rider and the rider's center of gravity and horizontal;

FIG. 10 is a side view illustration of the position of the rider on the snowmobile of the present invention, showing angle  $\theta$  formed between a line between the center of gravity of the snowmobile of the present invention with a rider and the rider's center of gravity and horizontal;

FIG. 11 is a side view illustration of the position of the rider on the snowmobile of the present invention, showing angle  $\phi$  formed by a line between the seat position and steering position and horizontal and also showing distance  $b$  between the steering position and seat position;

FIG. 12 is a side view illustration of the position of the rider on the snowmobile of the present invention, showing angle  $\Delta$  of the footrests that is formed between a forward position of the sideboard and horizontal;

FIG. 13 is a side view illustration of the position of the rider on the snowmobile of the present invention, showing angle  $\mu$  formed between a line through the seat position and the steering position and a line through the seat position and the top of the windshield;

FIG. 14 is a side view illustration of the position of the rider on the snowmobile of the present invention, showing angle  $\epsilon$  of the steering shaft over the engine;

FIG. 15 is a side view illustration of the position of the rider on the snowmobile of the present invention, showing the zones of variance of the seating and steering positions;

FIG. 16 is a side view illustration of the position of the rider on the snowmobile of the present invention, showing the calculations of  $\alpha_{\min}$  and  $\alpha_{\max}$ ;

FIG. 17 is a side view illustration of the position of the rider on the snowmobile of the present invention, showing the calculations of  $\beta_{\min}$  and  $\beta_{\max}$ ;

FIG. 18 is a side view illustration of the position of the rider on the snowmobile of the present invention, showing the calculations of  $\gamma_{\min}$  and  $\gamma_{\max}$ ;

FIG. 19 illustrates a front elevational view of a standard rider; and

FIG. 20 illustrates a side elevational view of the standard rider illustrated in FIG. 19.

#### Description of the Preferred Embodiments

Throughout the description of the various embodiments of the present invention, reference will be made to various elements, the construction of which is readily known to those skilled in the art. Accordingly, an exhaustive description of each and every component is not provided, only a description of those elements required for an understanding of the present invention.

FIG. 1 illustrates a conventional snowmobile 10 (that sold by Bombardier Inc. of Montreal, Canada, under the trademark SKI-DOO, model MXZ, model year 1999), which has a forward end 11 and a rearward end 13 (that are defined consistently with the travel direction of the vehicle). Conventional snowmobile 10 includes a body 12 (*i.e.*, the exterior upper portions) and a frame 14. While not shown in FIG. 1, an engine is carried by frame 14 at its forward end. In addition, two skis 16 are attached to the forward end of frame 14 through a suspension system 18. A drive track 20 is disposed under frame 14 and is connected operatively to the engine for propulsion of the vehicle.

At the front of frame 14, snowmobile 10 includes fairings 22 that enclose the engine to protect it and to provide a external shell that can be decorated so that the snowmobile is aesthetically pleasing. Typically the fairings 22 comprise a hood and a bottom pad (neither of which have been individually identified in the Figures). A windshield 24 may be connected to fairings 22 near the forward end 11 of snowmobile 10. Windshield 24 acts as a windscreen to lessen the force of the air on rider 26 when snowmobile 10 is moving.

A seat 28 extends from rearward end 13 of snowmobile 10 to the fairings 22. A steering device 32, such as a handlebar, is positioned forward of rider 26 and behind the engine. Two footrests 34 are positioned on either side of seat 28 to accommodate the rider's feet 46.

When seated, the average rider 26 will be positioned so that his hands grasp steering device 32 at steering position 36. Moreover, rider 26 will be seated so that the center of his torso 42 is above seat position 30. When seated in this manner, the rider's feet 46 naturally will be placed at footrest position 38. Positioned in this manner, the rider's center of gravity 40 will be located just forward of the rider's stomach, offset from the center of the rider's torso 42. (The rider's center of gravity 40 is offset forwardly from the center of the rider's torso 42 because the rider's arm and legs are disposed forward of the rider's torso 42 when rider 26 is in the driving position.)

For conventional snowmobile 10, the rider's center of gravity 40 is behind the center of gravity of the snowmobile 44 (*i.e.*, the center of gravity of the snowmobile with the rider). The center of gravity of the snowmobile 44 is located on or near the forward-most axle of drive track 20. (While the forward-most axle of drive track 20 is not shown, those skilled in the art will readily appreciate that it is located at or near the position labeled as the center of gravity of the vehicle 44.) The location of the center of gravity of the vehicle without the driver 44' is forward of the center of gravity of the vehicle with the driver 44. It is also lower than the center of gravity of the vehicle with the driver 44. In addition, footrests 34 are inclined upwardly from the horizontal so that the rider's feet 46 are in a comfortable position when rider 26 is seated on snowmobile 10.

For conventional snowmobile 10, the positioning of these various components and elements creates a situation where rider 26 is seated in a relatively upright position toward the rear of the vehicle. As shown in FIG. 1, with the rider's feet 46 positioned on footrests 34, the rider's knees 48 are positioned close to the steering position 36 where the rider's hands 50 are located. The placement of seat 28 is such that the seat position 30 is even with or slightly below the rider's knees 48. These elements, coupled with the placement of steering position 36 behind foot position 38, creates a situation where rider 26 sits inclined slightly forward, as indicated in FIG. 1.

The positioning of rider 26 shown in FIG. 1 is considered standard. Before the present invention, there was no motivation to adjust the position of rider 26 because the standard position does not hinder operation of the vehicle nor does it create an unsafe riding condition for rider 26. Moreover, the conventional positioning of rider 26 on snowmobile 10 does not prevent rider 26 from enjoying the sport of snowmobiling.

Despite this, the inventors of the present invention realized that it is possible to improve upon the construction of a snowmobile to alter the positioning of the rider to improve considerably the handling and ride of the vehicle.

FIG. 2 illustrates snowmobile 110, which is made according to the teachings of the present invention.

Like snowmobile 10, snowmobile 110 has a body 112 and a frame 114. Two skis 116 are positioned at the front of frame 114 so that snowmobile 110 may be steered over the snow. Skis 116 are connected to frame 114 through a suspension system 118 attached to frame 114 at its forward end. An engine (the position of which is shown generally in FIG. 14) is also disposed at the forward end of snowmobile 110 and is covered by fairings 122 that protect the engine and provide snowmobile 110

with an aesthetically pleasing appearance. A windshield 124 may extend upwardly from fairings 122 to act as a windscreen for rider 126.

A drive track 120, which is operatively connected to the engine, is positioned below frame 114. Drive track 120 is a continuous belt that runs around a number of axles including a forward-most axle 121 that is obscured by fairings 122 in FIG. 2 (but is illustrated in FIGS. 5-18). Forward-most axle 121 of snowmobile 110 is at or near the center of gravity 144 of snowmobile 110 with the rider, as would be understood by those skilled in the art. Further details in this respect are provided in connection with the discussion that accompanies FIGS. 5-18.

When rider 126 is on snowmobile 110, the rider will be positioned on seat 128 so that he occupies seat position 130. Seat position 130 is the point at which the weight of the rider 126 is exerted on the seat 128. This point may vary from rider to rider, given changes in height and weight from one rider to another. In cases of difficulty, it may be determined by taking a 50-percentile United States human male, placing him on the snowmobile in the position shown in the Figures (*i.e.*, that approximate the position of a rider a few seconds after starting the vehicle, heading straight ahead on a flat terrain), and drawing a line from his shoulder through his hip. (For purposes of this discussion, a standard person is illustrated in FIGS. 19 and 20.) The intersection of that line with the seat may be considered to be the seat position 130. It will also be understood that seat 128 will be covered with an amount of foam or similar padding-type material, and that the amount of that foam will vary from seat to seat. When the rider 126 sits upon the seat 128, his weight will cause the foam to compress and he will sink into the seat 128. Preferably, the seating position 130 is determined after this compression has occurred.

Steering device 132 is positioned at the forward end of snowmobile 110 and above the engine so that steering position 136 is forward of and above the center of gravity 144 of snowmobile 110. (For purposes of this discussion, the forward direction is toward forward end 111 of snowmobile 110 while the rearward direction is toward rearward end 113 of the vehicle.) As is the case with the seating position 130, the steering position 136 may vary depending on the size and shape of the hands of the rider 126. In cases of difficulty, the steering position 136 may be determined by placing the hands of the same 50-percentile rider described above, placing it on the steering device 132 in normal operating position. The steering position 136 will be the intersection of the center of the palm of the hands of the rider 126 and the steering device 132.

It should be noted that steering device 132 is shown in the various figures as a handlebar but should not be limited to just this particular construction. It would be understood by those skilled in the art that any suitable steering device may be used for snowmobile 110. For example, steering device 132 could be a steering wheel or a yoke of the type used in aircraft. Moreover, the positioning of steering device 132 above the engine also should not be considered to be limited to the position illustrated in FIG. 2. As would be understood by those skilled in the art, depending on the particular arrangement of elements for the snowmobile, it is possible that steering device 132 could be positioned

higher or lower than shown in FIG. 2 without departing from the scope and spirit of the present invention.

The rider's feet 146 rest on footrests 134 in footrest position 138 just behind the center of gravity of the vehicle 144. The footrest position 138 is in the location of the arch of the foot of the rider 126 when his feet are placed in normal operating position on the vehicle. Under normal operating conditions, the rider's feet 146 will rest on a forward portion of the sideboards. Preferably, toeholds are disposed above these forward portion and permit the rider to releasably secure himself to the vehicle.

As shown in FIG. 2 and more clearly in FIG. 5, rider 126 is positioned on snowmobile 110 so that a line passing through seat position 130 and steering position 136 forms an angle  $\alpha$  with a line passing through seat position 130 and footrest position 138. In addition, a line passing through footrest position 138 and steering position 136 forms an angle  $\beta$  with a line passing through footrest position 138 and seat position 130. Finally, a line passing through footrest position 138 and steering position 136 forms an angle  $\gamma$  with a line passing through steering position 136 and seat position 130. In other words, steering position 136, footrest position 138 and seat position 130 form a triangle with angles  $\alpha$ ,  $\beta$ , and  $\gamma$  that each fall within certain preferred ranges. For example, it is preferred that angle  $\alpha$  lie within a range of between about 63 and 152°, that angle  $\beta$  lie within a range of between about 16 and 84°, and that  $\gamma$  lie within a range of between about 11 and 42°. It is more preferred that angle  $\alpha$  lie within a range of between about 67 and 112°, that angle  $\beta$  lie within a range of between about 41 and 72°, and that  $\gamma$  lie within a range of between about 22 and 45°. It is even more preferred that angle  $\alpha$  lie within a range of between about 75 and 92°, that angle  $\beta$  lie within a range of between about 52 and 67°, and that  $\gamma$  lie within a range of between about 30 and 41°. Finally, it is most preferred that angle  $\alpha$  be about 83°, that angle  $\beta$  be about 64°, and that  $\gamma$  be about 33°. In addition, it is preferred that angles  $\alpha$ ,  $\beta$ , and  $\gamma$  be selected so that  $\alpha \geq \beta \geq \gamma$ . Moreover, it is preferred that the angles be selected to satisfy the following equation:  $\alpha \approx 2.5\gamma$ .

FIGS. 15-18 illustrate the ranges within which seat position 130 and steering position 136 may be varied while remaining within the scope of the present invention. The cross-hatched regions indicate the range within which steering position 136 and seat position 130 may fall depending upon the design of snowmobile 110 and the size and shape of rider 126.

When angles  $\alpha$ ,  $\beta$ , and  $\gamma$  satisfy any of the relationships set forth above, and preferably when steering position 136 is positioned forward of a vertical line passing through the vehicle's center of gravity 144, the rider's center of gravity 140 is positioned much closer to the center of gravity of the vehicle 144 than for conventional snowmobile 10 (as illustrated in FIG. 3). In addition, when rider 126 is positioned as illustrated in FIG. 2, the rider's feet 146 are more in line with his torso 142 and his center of gravity 140. This position has a number of advantages, as described in greater detail below.

When rider 26 is sitting on conventional snowmobile 10, if he sees a large bump ahead, it is natural for rider 26 to try to raise himself off of seat 28 to minimize the impact of the bump as he passes over it. However, because of his positioning on conventional snowmobile 10, in order for rider

26 to stand up, he must pull on steering device 32 using his upper body. The positioning of the rider's feet 46 forward of the rider's center of gravity 40 and at an incline on footrests 34 makes it difficult for rider 26 to stand on snowmobile 10 using only the strength of his legs. Moreover, even after rider 26 lifts himself from seat 28, his center of gravity 40 remains sufficiently rearward of the center of gravity of the vehicle 44 that he will perceive the large bump.

In snowmobile 110 of the present invention, however, a wholly different result is achieved. First, steering position 136 is displaced forward of the center of gravity of the vehicle 144. This position pulls rider 126 forward of the conventional position. By moving seat position 130 closer to the center of gravity of the vehicle 144 than the conventional example, and by redesigning footrests 134 so that they are kept at a decline, rider 126 is positioned so that, if a large bump is seen in the path ahead, rider 126 can easily raise himself from the seat using primarily the strength of only his legs 152. Since rider 126 is disposed closer to the center of gravity of the vehicle 144, when snowmobile 110 passes over a large bump, the effect of the bump is not transferred to rider 126 with the same magnitude as the force transferred to rider 26 on conventional snowmobile 10.

In addition, because rider 126 can raise himself from seat 128 using his legs 152 and not his arms 154, rider 126 can maintain greater control over snowmobile 110 as he passes over the obstacle than rider 26 on conventional snowmobile 10. If rider 26 (of conventional snowmobile 10) tries to pull himself from seat 28 as he passes over a large bump or obstacle, he sacrifices some of this strength pulling himself up from seat 28 and, therefore, may be less able to steer and control the vehicle as he passes over the obstacle.

To facilitate the rider's ability to raise himself off of seat 128 using his legs 152, footrests 134 are not inclined as with snowmobile 10. Instead, footrests 134 are part of the forward portion of the sideboards 135 that laterally extend from the frame below the seat on either side thereof. As a result, footrests 134 are at angle  $\Delta$  with respect to the horizontal. Preferably, angle  $\Delta$  is between about +10 and -20°. More preferably, angle  $\Delta$  lies between about +10 and -10°. Even more preferably, angle  $\Delta$  lies between about 0 and -5°. Most preferably, angle  $\Delta$  is about -5°.

As mentioned, one aspect of the present invention that improves upon the conventional snowmobile 10 is the fact that the rider's center of gravity 140 is closer to the center of gravity of the vehicle 144 than in the conventional example. This positioning helps to minimize the effect of bumps and terrain on rider 126. Referring to FIGS. 2 and 6, it is preferred that a distance  $x$ , measured as the distance between a vertical line 158 passing through the center of gravity of the vehicle 144 and a vertical line 160 passing through the center of gravity of the rider 140, be between about 0 and 50 cm. It is more preferred that distance  $x$  be between about 10 and 40 cm. In still a more preferred example, distance  $x$  is between about 22 and 32 cm. In the most preferred example, distance  $x$  is about 25 or 30 cm.

Also, a distance  $a$  between a vertical line passing through the center of gravity of the snowmobile without the rider 144' and a vertical line passing through the center of gravity of the

snowmobile with the rider 144 is preferably between about 0 and 14 cm. More preferably, distance  $a$  is between about 2 and 12 cm. Still more preferably, distance  $a$  is between about 4 and 10 cm. Still more preferably, distance  $a$  is between about 5 and 7 cm. Most preferably, distance  $a$  is about 5 cm.

Similarly, a distance  $z$  between a vertical line passing through the forward-most drive track axle 121 (usually, but not exclusively the drive axle) and a vertical line passing through the center of gravity of the rider 140 is preferably between about 15 and 65 cm. More preferably, distance  $z$  is between about 25 and 55 cm. Still more preferably, distance  $z$  is between about 35 and 55 cm. Still more preferably, distance  $z$  is between about 37 and 47 cm. Most preferably, distance  $z$  is about 40 cm or about 45 cm.

In addition, a distance  $y$  between a vertical line passing through the center of gravity of the snowmobile without the rider 144' and a vertical line passing through the center of gravity of the rider 140 is preferably between about 5 and 55 cm. More preferably, distance  $y$  is between about 15 and 45 cm. Still more preferably, distance  $y$  is between about 25 and 45 cm or between about 27 and 37 cm. Most preferably, distance  $y$  is about 30 or 35 cm.

Similarly, when rider 126 is positioned on snowmobile 110 so that his center of gravity 140 is closer to the center of gravity of the vehicle 144 than the conventional example, a line passing through the center of gravity of the vehicle 144 and the center of gravity of the rider 140 forms an angle  $\theta$  with horizontal 156 that preferably falls within a range between about 35 and 84°. More preferably, angle  $\theta$  lies between 45 and 75°. Still more preferably, angle  $\theta$  lies within a range between about 55 and 70°. Finally, angle  $\theta$  is about 57°.

In this regard, snowmobile 110 has a center of gravity positioned so that a line passing through the forward-most drive track axle 121 and the center of gravity of the rider 140 preferably forms an angle  $\pi$  with horizontal that is between about 41 and 75°. More preferably, angle  $\pi$  is between about 45 and 65°. Still more preferably, angle  $\pi$  is between about 50 and 60°. Most preferably, angle  $\pi$  is about 55°.

Snowmobile 110 has a center of gravity positioned so that a line passing through the center of gravity of the snowmobile without the rider 144' and the center of gravity of the snowmobile with the rider 144 preferably forms an angle  $\lambda$  with horizontal that is between about 35 and 90°. More preferably, angle  $\lambda$  is between about 50 and 90°. Still more preferably, angle  $\lambda$  is between about 62 and 90°. Most preferably, angle  $\lambda$  is about 67°.

Snowmobile 110 has a center of gravity positioned so that a line passing through the center of gravity of the snowmobile without the rider 144' and the center of gravity of the rider 140 preferably forms an angle  $\omega$  with horizontal that is between about 39 and 79°. More preferably, angle  $\omega$  is between about 49 and 69°. Still more preferably, angle  $\omega$  is between about 54 and 64°. Most preferably, angle  $\omega$  is about 59°.

In addition, when rider 126 is positioned on snowmobile 110 so that his center of gravity 140 is closer to the center of gravity of the vehicle 144 than in conventional snowmobile 10, a distance  $b$

between a vertical line passing through steering position 136 and a vertical line passing through seat position 130 is between about 40 and 90 cm. Preferably, distance  $b$  is between about 60 and 80 cm. Most preferably, distance  $b$  (in FIG. 2) is either 65 or 70 cm.

Furthermore, as shown in FIG. 11, with the steering position 136 and seat position 130 located so that the center of gravity of the rider 140 is closer to the center of gravity of the vehicle 144 than the conventional example, a line passing through steering position 136 and seat position 130 forms an angle  $\phi$  with horizontal 156 that lies in a range between about 15 and 51°. More preferably, angle  $\phi$  lies in a range between about 19 and 41°. Even more preferably, angle  $\phi$  lies in a range between about 23 and 31°. Most preferably, angle  $\phi$  is about 26°.

To improve the steerability of snowmobile 110, the inventors also altered the positioning of the axis of the steering shaft 162 so that it is more steeply sloped than the steering shaft in prior art snowmobiles having a steering shaft over the engine. With a steeper slope to the axis of the steering shaft 162, the turning force applied by rider 126 is more directly applied to steer the vehicle. According to the present invention, and as illustrated in FIGS. 2 and 14, the axis of the steering shaft 162 forms an angle  $\epsilon$  with vertical 164 that is less than 45°. More preferably, angle  $\epsilon$  lies between about 25 and 40°. Even more preferably, angle  $\epsilon$  lies between about 30 and 35°. Most preferably, angle  $\epsilon$  is about 33°. The angular position of the steering shaft 162 is also preferred because it facilitates placement of steering position 136 in a position forward of that for conventional snowmobile 10.

Positioning rider 126 on snowmobile 110 in the manner described has still further advantages. Windshield 124 has a top 166. When snowmobile 110 is moving, top 166 of windshield 166 defines a point from which the air travels along a travel path 168. The air along air travel path will have laminar flow characteristics until it reaches a turbulent flow region 170. When rider 126 is positioned on snowmobile 110 as described above, the rider's head 172 falls within the laminar flow region 174. As a result, rider 126 enjoys a more comfortable ride because the air has a less adverse effect on his head 172 in terms of temperature, noise, etc.

Those skilled in the art will readily recognize that the positioning of the rider's head 172 on snowmobile 110 is very different than that for conventional snowmobile 10. As illustrated in FIG. 3, head 72 of rider 26 falls into the turbulent flow region 170. Accordingly, rider 26 experiences a poorer quality ride than rider 126.

The positioning of rider 126 on snowmobile 110 in the manner taught by the present invention offers still further advantages. As illustrated, the view that rider 126 has of the ground in front of him is much improved over the view of the ground in front of rider 26 on conventional snowmobile 26. This is true because rider 126 has less of the snowmobile fairings 122 and windshield 124 in front of him than rider 26 does. As a result, rider 126 is better able to react to obstacles in his immediate path than rider 26.



The height of the windshield 124, the location of seat position 130 and the location of steering position 136 define a relationship that facilitates construction of a snowmobile 110 where the view of the rider is improved. Specifically, a line between the top 166 of windshield 124 and seat position 130 forms an angle  $\mu$  with a line between steering position 136 and seat position 130 that lies between about 0 and 20°. Preferably, angle  $\mu$  lies between about 10 and 20°. Most preferably, angle  $\mu$  is about 18°.

The design of snowmobile 110 offers still further advantages. For example, as illustrated in FIG. 1, the rider's knees 48 are positioned very close to steering position 36. As a result, when rider 26 steers snowmobile 10, it is not uncommon for rider 26 to hit his knees 48 with steering device 32. This presents a minor design difficulty that the present invention solves.

As shown in FIG. 4, when rider 126 turns steering device 32 to its maximum positions, the handlebars sweep out a handlebar space 176. Because steering device 132 is positioned forward of the center of gravity of the vehicle 144, handlebar space 176 cannot intersect with the space occupied by rider 126. In other words, rider 126 will not normally hit his knees 148 with steering device 132 while riding snowmobile 110.

Snowmobile 110 of the present invention also differs from conventional snowmobile 10 in that the steering device 132 is disposed forward of the axis of the forward-most drive axle, which corresponds closely to the center of gravity of the vehicle 144. Steering device 132 is also positioned forward of footrest position 138, which also differs from conventional snowmobile 10. With steering position 136 disposed forward of both the center of gravity of the vehicle 144 and forward of the footrest position 138, the center of gravity of the rider 140 is positioned much closer to the center of gravity of the vehicle 144 than in conventional snowmobile 10.

The present invention offers still further advantages over the design of conventional snowmobile 10. Since rider 126 is positioned closer to the center of gravity of the vehicle 144, the ride for a second rider on the same vehicle is also improved because the second occupant is also disposed closer to the center of gravity of the vehicle. FIG. 3 is illustrative.

Rider 26 (who is shown astride conventional snowmobile 10) is essentially in the second passenger seat for snowmobile 110. Since rider 126 has been moved forward, the second rider is subject to the kind of forces that he would be subjected to if he were driving a conventional snowmobile 10. In other words, the second rider is no worse off than he would be if he were passenger 26 on conventional snowmobile 10. Indeed the second rider's situation is quite improved, and may approach that of a rider 26 on a conventional snowmobile 10.

In addition, since second rider experiences a similar ride experience to what rider 26 experiences on conventional snowmobile, it is possible that a third rider could be added to snowmobile 110 behind the second rider. The third rider, then, would experience the forces similar to those that a second rider would normally experience on conventional snowmobile 10.

While the invention has been described with reference to several preferred embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted for elements thereof without departing from the spirit and scope of the present invention. In addition, many modifications may be made to adapt a particular situation, component, or material to the teachings of the present invention without departing from its teachings as claimed.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000

## CLAIMS

1. A snowmobile, comprising:
  - a frame;
  - an engine disposed on the frame;
  - a drive track disposed below the frame and connected operatively to the engine for propulsion of the snowmobile;
  - at least one ski disposed on the frame;
  - a seat disposed on the frame, suitable for a rider with a center of gravity; and
  - a steering device disposed on the frame forward of the seat, the steering device being operatively connected to the at least one ski for steering the snowmobile,
  - wherein the snowmobile has a first center of gravity without the rider and a second center of gravity with the rider, and
  - wherein a distance between a vertical line passing through the first center of gravity and a vertical line passing through the second center of gravity is between about 0 cm and 14 cm.
2. The snowmobile of claim 1, wherein the distance is between about 2 and 12 cm.
3. The snowmobile of claim 2, wherein the distance is between about 4 and 10 cm.
4. The snowmobile of claim 3, wherein the distance is between about 5 and 7 cm.
5. The snowmobile of claim 4, wherein the distance is about 5 cm.
6. A snowmobile, comprising:
  - a frame;
  - an engine disposed on the frame;
  - a drive track disposed below the frame and connected operatively to the engine for propulsion of the snowmobile;
  - at least one ski disposed on the frame;
  - a seat disposed on the frame, suitable for a rider with a center of gravity; and
  - a steering device disposed on the frame forward of the seat, the steering device being operatively connected to the at least one ski for steering the snowmobile,
  - wherein the snowmobile has a first center of gravity without the rider and a second center of gravity with the rider, and
  - wherein a line passing through the first center of gravity of the snowmobile and the second center of gravity forms an angle with horizontal that is between about 35 and 90°.

7. The snowmobile of claim 6, wherein the angle is between about 50 and 90°.
8. The snowmobile of claim 7, wherein the angle is between about 62 and 90°.
9. The snowmobile of claim 8, wherein the angle is about 67°.
10. A snowmobile, comprising:
  - a frame;
  - an engine disposed on the frame;
  - a drive track disposed below the frame and connected operatively to the engine for propulsion of the snowmobile;
  - a forward-most drive track axle disposed on the frame;
  - at least one ski disposed on the frame;
  - a seat disposed on the frame, suitable for a rider with a center of gravity;
  - a steering device disposed on the frame forward of the seat, the steering device being operatively connected to the at least one ski for steering the snowmobile; and
  - wherein a distance between a vertical line passing through the forward-most drive track axle and a vertical line passing through the center of gravity of the rider is between about 15 and 65 cm.
11. The snowmobile of claim 10, wherein the distance is between about 25 and 55 cm.
12. The snowmobile of claim 11, wherein the distance is between about 35 and 55 cm.
13. The snowmobile of claim 12, wherein the distance is between about 37 and 47 cm.
14. The snowmobile of claim 13, wherein the distance is about 40 cm.
15. The snowmobile of claim 14, wherein the distance is about 45 cm.
16. A snowmobile, comprising:
  - a frame;
  - an engine disposed on the frame;
  - a drive track disposed below the frame and connected operatively to the engine for propulsion of the snowmobile;
  - a forward-most drive track axle disposed on the frame;
  - at least one ski disposed on the frame;
  - a seat disposed on the frame, suitable for a rider having a center of gravity;

a steering device disposed on the frame forward of the seat, the steering device being operatively connected to the at least one ski for steering the snowmobile; and

wherein a line passing through the forward-most drive track axle and the center of gravity of the rider forms an angle with horizontal that is between about 41 and 75°.

17. The snowmobile of claim 16, wherein the angle is between about 45 and 65°.

18. The snowmobile of claim 17, wherein the angle is between about 50 and 60°.

19. The snowmobile of claim 18, wherein the angle is about 55°.

20. A snowmobile, comprising:

a frame;

an engine disposed on the frame;

a drive track disposed below the frame and connected operatively to the engine for propulsion of the snowmobile;

at least one ski disposed on the frame;

a seat disposed on the frame, suitable for a rider with a center of gravity; and

a steering device disposed on the frame forward of the seat, the steering device being operatively connected to the at least one ski for steering the snowmobile,

wherein the snowmobile has a center of gravity without the rider, and

wherein a distance between a vertical line passing through the center of gravity of the snowmobile without the rider and a vertical line passing through the center of gravity of the rider is between about 5 and 55 cm.

21. The snowmobile of claim 20, wherein the distance is between about 15 and 45 cm.

22. The snowmobile of claim 21, wherein the distance is between about 25 and 45 cm.

23. The snowmobile of claim 22, wherein the distance is between about 27 and 37 cm.

24. The snowmobile of claim 23, wherein the distance is about 30 cm.

25. The snowmobile of claim 24, wherein the distance is about 35 cm.

26. A snowmobile, comprising:

a frame;

an engine disposed on the frame;  
 a drive track disposed below the frame and connected operatively to the engine for propulsion of the snowmobile;  
 at least one ski disposed on the frame;  
 a seat disposed on the frame, suitable for a rider having a center of gravity; and  
 a steering device disposed on the frame forward of the seat, the steering device being operatively connected to the at least one ski for steering the snowmobile,  
 wherein the snowmobile has a center of gravity without the rider, and  
 wherein a line passing through the center of gravity of the snowmobile without the rider and the center of gravity of the rider forms an angle with horizontal that is between about 39 and 79°.

27. The snowmobile of claim 26, wherein the angle is between about 49 and 69°.

28. The snowmobile of claim 27, wherein the angle is between about 54 and 64°.

29. The snowmobile of claim 28, wherein the angle is about 59°.

30. A snowmobile, comprising:  
 a frame;  
 an engine disposed on the frame;  
 a drive track disposed below the frame and connected operatively to the engine for propulsion of the snowmobile;  
 at least one ski disposed on the frame;  
 a seat disposed on the frame, suitable for a rider with a center of gravity; and  
 a steering device disposed on the frame forward of the seat, the steering device being operatively connected to the at least one ski for steering the snowmobile,  
 wherein the snowmobile has a center of gravity with the rider, and  
 wherein a distance between a vertical line passing through the center of gravity of the snowmobile with the rider and a vertical line passing through the center of gravity of the rider is between about 0 and 50 cm.

31. The snowmobile of claim 30, wherein the distance is between about 10 and 40 cm.

32. The snowmobile of claim 31, wherein the distance is between about 20 and 40 cm.

33. The snowmobile of claim 32, wherein the distance is between about 22 and 32 cm.

34. The snowmobile of claim 33, wherein the distance is about 25 cm.
35. The snowmobile of claim 34, wherein the distance is about 30 cm.
36. A snowmobile, comprising:
  - a frame;
  - an engine disposed on the frame;
  - a drive track disposed below the frame and connected operatively to the engine for propulsion of the snowmobile;
  - at least one ski disposed on the frame;
  - a seat disposed on the frame, suitable for a rider having a center of gravity; and
  - a steering device disposed on the frame forward of the seat, the steering device being operatively connected to the at least one ski for steering the snowmobile,
  - wherein the snowmobile has a center of gravity with the rider, and
  - wherein a line passing through the center of gravity of the snowmobile with the rider and the center of gravity of the rider forms an angle with horizontal that is between about 35 and 84°.
37. The snowmobile of claim 36, wherein the angle is between about 45 and 75°.
38. The snowmobile of claim 37, wherein the angle is between about 55 and 70°.
39. The snowmobile of claim 38, wherein the angle is about 57°.
40. A snowmobile, comprising:
  - a frame;
  - a seat disposed on the frame, suitable for a rider;
  - a steering device disposed on the frame forward of the seat; and
  - right and left footrests disposed below the seat on either side thereof, suitable for placement of the rider's feet thereon,
  - wherein the seat defines a seat position, the steering device defines a steering position, and the footrests define a footrest position,
  - wherein a line passing through the seat position and the steering position forms angle  $\alpha$  with a line passing through the seat position and the footrest position;
  - wherein a line passing through the footrest position and the steering position forms angle  $\beta$  with the line passing through the footrest position and the seat position,
  - wherein the line passing through the footrest position and the steering position forms angle  $\gamma$  with the line passing through the steering position and the seat position, and

wherein angle  $\alpha$  is between about 63 and 152°, angle  $\beta$  is between about 16 and 84°, and angle  $\gamma$  is between about 11 and 42°.

41. The snowmobile of claim 40, wherein angle  $\alpha$  is between about 67 and 112°, angle  $\beta$  is between about 41 and 72°, and angle  $\gamma$  is between about 22 and 45°.

42. The snowmobile of claim 41, wherein angle  $\alpha$  is between about 75 and 97°, angle  $\beta$  is between about 52 and 67°, and angle  $\gamma$  is between about 30 and 41°.

43. The snowmobile of claim 42, wherein angle  $\alpha$  is about 83°, angle  $\beta$  is about 64°, and angle  $\gamma$  is about 33°.

44. A snowmobile, comprising:

a frame;

a seat disposed on the frame, suitable for a rider;

a steering device disposed on the frame forward of the seat; and

right and left footrests disposed below the seat on either side thereof, suitable for placement of the rider's feet thereon;

wherein the seat defines a seat position, the steering device defines a steering position, and the footrests define a footrest position,

wherein a line passing through the seat position and the steering position forms angle  $\alpha$  with a line passing through the seat position and the footrest position;

wherein a line passing through the footrest position and the steering position forms angle  $\beta$  with the line passing through the footrest position and the seat position,

wherein the line passing through the footrest position and the steering position forms angle  $\gamma$  with the line passing through the steering position and the seat position, and

wherein angle  $\alpha$ , angle  $\beta$ , and angle  $\gamma$  satisfy the relationship  $\alpha \geq \beta \geq \gamma$ .

45. A snowmobile, comprising:

a frame;

a seat disposed on the frame, suitable for a rider;

a steering device disposed on the frame forward of the seat; and

right and left footrests disposed below the seat on either side thereof, suitable for placement of the rider's feet thereon;

wherein the seat defines a seat position, the steering device defines a steering position, and the footrests define a footrest position,



wherein a line passing through the seat position and the steering position forms angle  $\alpha$  with a line passing through the seat position and the footrest position;

wherein a line passing through the footrest position and the steering position forms angle  $\beta$  with the line passing through the footrest position and the seat position,

wherein the line passing through the footrest position and the steering position forms angle  $\gamma$  with the line passing through the steering position and the seat position, and

wherein angle  $\alpha$ , angle  $\beta$ , and satisfy the relationship  $\alpha \approx 2.5\gamma$ .

46. A snowmobile, comprising:

a frame;

a seat disposed on the frame; and

a steering device disposed on the frame forward of the seat;

wherein the seat defines a seat position and the steering device defines a steering position, and

wherein a line passing through the steering position and the seat position forms an angle  $\phi$  with horizontal that is between about 15 and 51°.

47. The snowmobile of claim 46, wherein angle  $\phi$  is between about 19 and 41°.

48. The snowmobile of claim 47, wherein angle  $\phi$  is between about 23 and 31°.

49. The snowmobile of claim 48, wherein angle  $\phi$  is about 26°.

50. A snowmobile, comprising:

a frame;

an engine disposed on the frame;

at least one ski disposed on the frame;

a steering shaft operatively connected to the at least one ski for steering the snowmobile, the steering shaft being disposed over the engine at an angle  $\epsilon$  of less than about 45° from vertical.

51. The snowmobile of claim 50, wherein angle  $\epsilon$  is between about 25 and 40° from vertical.

52. The snowmobile of claim 51, wherein angle  $\epsilon$  is between about 30 and 35° from vertical.

53. The snowmobile of claim 52, wherein angle  $\epsilon$  is about 33° from vertical.

54. A snowmobile, comprising:

a frame;

a seat disposed on the frame, suitable for a rider, the seat defining a location of a rider space associated with the seat;

a steering shaft disposed on the frame forward of the seat; and

a handlebar mounted onto the steering shaft,

wherein the handlebar and steering shaft are rotatable about a central axis between first and second positions to define a handlebar space, and

wherein the handlebar space does not intersect with the rider space.

55. A snowmobile, comprising:

a frame;

a seat disposed on the frame, suitable for a rider;

a steering device disposed forward of the seat; and

a windshield disposed forward of the steering device, the windshield having a top;

wherein the seat defines a seat position and the steering device defines a steering position, and

wherein a line between the steering position and the seat position forms an angle  $\mu$  with a line between the seat position and the top of the windshield that lies between about 0 and 20°.

56. The snowmobile of claim 55, wherein angle  $\mu$  is between about 10 and 20°.

57. The snowmobile of claim 56, wherein angle  $\mu$  is about 18°.

58. A snowmobile, comprising:

a frame;

a seat disposed on the frame, suitable for a rider;

a steering device disposed forward of the seat; and

a windshield disposed forward of the seat, the windshield having a top;

wherein, when in motion, the windshield defines a laminar flow region of moving air that extends upwardly and rearwardly from the top thereof, and

wherein, when seated in the seat and when grasping the steering device, the rider's head is positioned within the laminar flow region.

59. A snowmobile, comprising:

a frame;

a forward-most drive track axle disposed on the frame; and

a steering device disposed on the frame forward of the forward-most drive track axle.

60. A snowmobile, comprising:

a frame;  
 a steering device disposed on the frame;  
 wherein the snowmobile has a center of gravity without a rider and the steering device is disposed on the frame forward of the center of gravity.

61. A snowmobile, comprising:

a frame;  
 a steering device disposed on the frame;  
 wherein the snowmobile has a center of gravity with a rider and the steering device is disposed on the frame forward of the center of gravity.

62. A snowmobile, comprising:

a frame;  
 a seat disposed on the frame, suitable for a rider;  
 right and left footrests disposed below the seat on either side thereof, suitable for placement of the rider's feet thereon; and  
 a steering device disposed forward of the footrests.

63. A snowmobile, comprising:

a frame;  
 a seat disposed on the frame, suitable for a rider;  
 right and left sideboards extending laterally from the frame below the seat on either side thereof, each of the sideboards having a forward portion suitable for placement of the rider's feet thereon;  
 right and left toe-holds disposed respectively above the forward portion of each sideboard for allowing the rider to releasably secure himself to the snowmobile;  
 a steering device disposed forward of the forward portions of the sideboards.

64. A snowmobile, comprising:

a frame;  
 a seat disposed on the frame, defining a seat position;  
 a steering device disposed on the frame and forward of the seat defining a steering position,  
 wherein a distance between vertical lines passing through the steering position and the seat position is between about 40 and 90 cm.

65. The snowmobile of claim 64, wherein the distance is between about 50 and 80 cm.

66. The snowmobile of claim 65, wherein the distance is between about 60 and 80 cm.

67. The snowmobile of claim 66, wherein the distance is about 65 cm.
68. The snowmobile of claim 67, wherein the distance is about 70 cm.
69. A snowmobile, comprising:  
a frame;  
a seat disposed on the frame, suitable for a rider; and  
right and left footrests disposed below the seat on either side thereof, suitable for placement of the rider's feet thereon, the footrests disposed at an angle  $\Delta$  with horizontal that is between about +10 and -20°.
70. The snowmobile of claim 69, wherein angle  $\Delta$  is between about +10 and -10°.
71. The snowmobile of claim 70, wherein angle  $\Delta$  is between about 0 and -5°.
72. The snowmobile of claim 71, wherein angle  $\Delta$  is about -5°.
73. A snowmobile, comprising:  
a frame;  
a seat disposed on the frame, suitable for a rider;  
right and left sideboards extending laterally from the frame below the seat on either side thereof, each of the sideboards having a forward portion suitable for placement of a rider's foot thereon, the forward portion of each sideboard disposed at an angle  $\Delta$  with horizontal that is between about +10 and -20°;  
right and left toe-holds disposed respectively above the forward portion of each sideboard for allowing the rider to releasably secure himself to the snowmobile.
74. The snowmobile of claim 73, wherein angle  $\Delta$  is between about +10 and -10°.
75. The snowmobile of claim 74, wherein angle  $\Delta$  is between about 0 and -5°.
76. The snowmobile of claim 75, wherein angle  $\Delta$  is about -5°.
77. A snowmobile, comprising:  
a frame;  
a seat disposed on the frame, suitable for a rider;

a steering device disposed on the frame forward of the seat; and

right and left sideboards extending laterally from the frame below the seat on either side thereof, each of the sideboards having a forward portion suitable for placement of a rider's foot thereon,

wherein the seat defines a seat position, the steering device defines a steering position, and the forward portions of the sideboards define a footrest position,

wherein a line passing through the seat position and the steering position forms angle  $\alpha$  with a line passing through the seat position and the footrest position;

wherein a line passing through the footrest position and the steering position forms angle  $\beta$  with the line passing through the footrest position and the seat position,

wherein the line passing through the footrest position and the steering position forms angle  $\gamma$  with the line passing through the steering position and the seat position, and

wherein angle  $\alpha$  is between about 63 and 152°, angle  $\beta$  is between about 16 and 84°, and angle  $\gamma$  is between about 11 and 42°.

78. The snowmobile of claim 77, wherein angle  $\alpha$  is between about 67 and 112°, angle  $\beta$  is between about 41 and 72°, and angle  $\gamma$  is between about 22 and 45°.

79. The snowmobile of claim 78, wherein angle  $\alpha$  is between about 75 and 97°, angle  $\beta$  is between about 52 and 67°, and angle  $\gamma$  is between about 30 and 41°.

80. The snowmobile of claim 79, wherein angle  $\alpha$  is about 83°, angle  $\beta$  is about 64°, and angle  $\gamma$  is about 33°.

81. A snowmobile, comprising:

a frame;

a seat disposed on the frame, suitable for a rider;

a steering device disposed on the frame forward of the seat; and

right and left sideboards extending laterally from the frame below the seat on either side thereof, each of the sideboards having a forward portion suitable for placement of a rider's foot thereon,

wherein the seat defines a seat position, the steering device defines a steering position, and the forward portions of the sideboards define a footrest position,

wherein a line passing through the seat position and the steering position forms angle  $\alpha$  with a line passing through the seat position and the footrest position;

wherein a line passing through the footrest position and the steering position forms angle  $\beta$  with the line passing through the footrest position and the seat position,

wherein the line passing through the footrest position and the steering position forms angle  $\gamma$  with the line passing through the steering position and the seat position, and  
 wherein angle  $\alpha$ , angle  $\beta$ , and angle  $\gamma$  satisfy the relationship  $\alpha \geq \beta \geq \gamma$ .

82. A snowmobile, comprising:

a frame;  
 a seat disposed on the frame, suitable for a rider;  
 a steering device disposed on the frame forward of the seat; and  
 right and left sideboards extending laterally from the frame below the seat on either side thereof, each of the sideboards having a forward portion suitable for placement of a rider's foot thereon,

wherein the seat defines a seat position, the steering device defines a steering position, and the forward portions of the sideboards define a footrest position,

wherein a line passing through the seat position and the steering position forms angle  $\alpha$  with a line passing through the seat position and the footrest position;

wherein a line passing through the footrest position and the steering position forms angle  $\beta$  with the line passing through the footrest position and the seat position,

wherein the line passing through the footrest position and the steering position forms angle  $\gamma$  with the line passing through the steering position and the seat position, and

wherein angle  $\alpha$ , angle  $\beta$ , and satisfy the relationship  $\alpha \approx 2.5\gamma$ .

83. The snowmobile of any one of claims 77 to 82 further comprising:

right and left toe-holds disposed respectively above the forward portion of each sideboard for allowing the rider to releasably secure himself to the snowmobile.

**ABSTRACT**

A snowmobile is described having a frame and an engine disposed on the frame. A drive track is disposed below the frame and connected operatively to the engine for propulsion of the snowmobile. At least one ski is disposed on the frame. A seat is disposed rearwardly of the engine, suitable for a rider with a center of gravity, and a steering device is disposed above the engine and forward of the seat, the steering device being operatively connected to the at least one ski for steering the snowmobile. The snowmobile has a center of gravity positioned such that a distance between a vertical line passing through the center of gravity of the snowmobile and a vertical line passing through the center of gravity of the rider is within a predetermined range. Also, the distance between the steering position of the snowmobile and the seat position of the rider falls within a predetermined range. The rider is positioned on the snowmobile such that lines passing through the steering position, the seat position, and the footrest position form a triangle with angles  $\alpha$ ,  $\beta$ , and  $\gamma$  that have a specific relationship to one another. In addition, the steering position is disposed forward of the forward-most drive axle of the drive track. The footrests are positioned below the seat at a declining angle  $\Delta$  to the horizontal. The axis of the steering column of the snowmobile forms an angle  $\epsilon$  with vertical that falls within a predetermined range. A line passing through the steering position and the seat position forms an angle  $\phi$  with the horizontal that falls within a predetermined range. A line passing through the center of gravity of the vehicle and the center of gravity of the rider forms an angle  $\theta$  with the horizontal that falls within a specified range. Finally, the position of the rider is such that the head of the rider naturally falls within a laminar air flow region that is defined by the windshield of the snowmobile.

Downloaded from ascelibrary.org by University of California, San Diego on 06/01/15. Copyright ASCE, For All Rights Reserved, No part of this document may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage or retrieval system, without permission in writing from ASCE.





FIG. 1










FIG. 4






FIG. 6




FIG. 7






FIG. 9






FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16









FIG. 18



**FIG. 19**




FIG. 20

ORIGINAL/SUBSTITUTE/SUPPLEMENTAL  
DECLARATIONSFOR PATENT APPLICATION  
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name, and I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the INVENTION ENTITLED SNOWMOBILE

the specification of which (CHECK applicable BOX(ES))  
☒ A. ☒ is attached hereto.  
☐ B. ☐ was filed on \_\_\_\_\_ as U.S. Application No. \_\_\_\_\_  
☐ C. ☐ was filed as PCT International Application No. PCT/\_\_\_\_\_/\_\_\_\_\_, on \_\_\_\_\_  
 and (if applicable to U.S. or PCT application) was amended on \_\_\_\_\_

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose all information known to me to be material to patentability as defined in 37 C.F.R. 1.56. Except as noted below, I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 385(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International Application which designated at least one other country than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT International Application, filed by me or my assignee disclosing the subject matter claimed in this application and having a filing date (1) before that of the application on which priority is claimed, or (2) if no priority claimed, before the filing date of this application:

## PRIOR FOREIGN APPLICATION(S)

Number	Country	Date first Laid-open or Published	Date Patented or Granted	Priority NOT Claimed
2,256,944	CANADA	23/December/1998		

If more prior foreign applications, X box at bottom and continue on attached page.

Except as noted below, I hereby claim domestic priority benefit under 35 U.S.C. 119(e) or 120 and/or 385(c) of the indicated United States applications listed below and PCT International applications listed above or below and, if this is a continuation-in-part (CIP) application, insofar as the subject matter disclosed and claimed in this application is in addition to that disclosed in such prior applications, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in 37 C.F.R. 1.56 which became available between the filing date of each such prior application and the national or PCT international filing date of this application:

## PRIOR U.S. PROVISIONAL, NONPROVISIONAL AND/OR PCT APPLICATION(S)

Application No. (series code/serial no.)	Date/MONTH/Year Filed	Status	Priority NOT Claimed
80/187,814	28/November/1999	pending, abandoned, patented	pending

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

And I hereby appoint Pillsbury Madison & Sutro LLP, Intellectual Property Group, 1100 New York Avenue, N.W., Ninth Floor, East Tower, Washington, D.C. 20005-3918, telephone number (202) 851-3000 (to whom all communications are to be directed), and the below-named persons (of the same address) individually and collectively my attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith and with the resulting patent, and I hereby authorize them to delete names/numbers below of persons no longer with their firm and to act and rely on instructions from and communicate directly with the person/assignee/attorney/firm/organization who/which first sends/sent this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instruct the above firm and/or a below attorney in writing to the contrary.

Paul N. Kokulis	18773	Dale S. Lazer	28872	Mark G. Paulson	30793	Michael R. Dzwonczyk	36767
Raymond F. Lippitt	17519	Paul E. White, Jr.	32011	Stephen C. Glazier	31381	W. Patrick Bengtsson	32456
G. Lloyd Knight	17698	Glenn J. Perry	28458	Paul F. McQuade	31542	Jack S. Barufka	37067
Carl G. Love	18781	Kendrew H. Colton	30368	Ruth N. Morduch	31044	Adam R. Hess	41835
Kevin E. Joyce	20508	G. Paul Edgell	24236	Richard H. Zaitlen	27248	Jeffrey D. Karceski	35914
George M. Silita	18221	Lynn E. Eccleston	35861	Roger R. Wise	31204		
Donald J. Bird	25323	Timothy J. Kama	34852	Jay M. Finkelstein	21082		
Peter W. Gowday	25872	David A. Jekopin	42995	Anita M. Kirkpatrick	32617		

## (1) INVENTOR'S SIGNATURE:

Date: 23/12/1999

Bruno	GIRQUARD
Residence	Quebec/Canada
Post Office Address	180 Grande Ligne, Bonsecours, Quebec JOE 1H0, Canada
(Include Zip Code)	JOE 1H0

## (2) INVENTOR'S SIGNATURE:

Date: 23/12/1999

Bethold	PECTEAU
Residence	Richmond
Post Office Address	695 Des Erables (P.O. Bx 1677), Richmond, Quebec JOB 2H0, Canada
(Include Zip Code)	JOB 2H0

FOR ADDITIONAL INVENTORS, "X" box ☐ and proceed on the attached page to list each additional inventor.  
☐ See additional foreign priorities on attached page (incorporated herein by reference).

Atty. Dkt. No. PM 9919/265/136  
 (M#)